

Wave Hot&Cold

Every type of water,
when you want it, at home.

The built-in water dispenser

Wave dispenses 4 types of water: microfiltered water at room temperature, cold microfiltered water, sparkling cold microfiltered water and hot water at 85°C.
Wave is available at a height of 45cm for built-in installation.
Wave controls have soft-touch technology, without any buttons.
Wave is designed both for the use of disposable CO2 cylinders (standard) and for external rechargeable cylinders.
The carbon dioxide consumption depends on how sparkling you want the water. Wave is available in stainless steel, black glass and De Castelli material.

TECHNICAL SPECIFICATIONS Wave 45 Hot&Cold	
Compressor power	1/11Hp
Voltage	230 V - 1Ph - 50/60 Hz
Production of cold and sparkling water	15 l/h
Adjustable gassing system	min.- max 2 ÷ 3.5 bar
Adjustable cold water temperature	from 5 to 12°C
Hot water temperature	85°C +/- 1°C
Water inlet pressure	2 ÷ 3.5 bar
Max absorbed power	810 W
Disposable CO2 cylinder capacity	600 g
Cold line (hot line) purifying filter service life	2.700 Lt / 1 year (1700 Lt / 6 months)
Net built-in machine weight	35 kg
Refrigerant gas	R600

Standard equipment: Certified NSF class 1 filter (cold line) / Hot water filter.
Option: 600g disposable CO2 cylinder / Rechargeable 1kg CO2 cylinder kit including connection pipe / Rechargeable 4kg CO2 cylinder kit including connection pipe.

Finishes

It is possible to customise the finish of all Wave models: brushed steel, black glass, front panels in various colours and De Castelli finishes. (See page 84)

Assembly precautions

For proper use, the purification filters and the CO2 cylinder need to be checked. The filter (cold line) inside the appliance has a service life of 2700 litres or 1 year. The filter (hot line) has a service life of 1700 litres.

For appropriate operation of the household appliance, the filters must always be in good condition. When the filters run out, the water supply is not interrupted, but a warning signal to change the filter is emitted.

Replacement is recommended between 6 months and 1 year, according to the water hardness and the quantity of hot water dispensed.

Built-in Wave Hot&Cold 45



L 595 mm
D 547 mm
H 450 mm

