Vinoteca

Vinoteca provides perfect storage for the most valuable wines.

The wine cabinet.

Available in 3-dimension built-in version, with black glass finish.
Vinoteca 60 is equipped with 3 sliding beech shelves (2 shelves to hold Bordeaux bottles, 1 shelf to hold Magnum bottles), while Vinoteca 45 has 2 sliding beech shelves (to hold Bordeaux bottles).

The electronic control panel is set on the inside and the temperature can be read on the touchpad electronic display. Vinoteca is fitted with a second-generation push-open system and the adjustable LED lighting creates an elegant display ambiance.

TECHNICAL SPECIFICATIONS	Dual-temperature Vinoteca 60	Single-temperature Vinoteca 45	Single-temperature Vinoteca 15
Power	100 W	85 W	130 W
Voltage	220 / 240 V - 50 Hz	220 / 240 V - 50 Hz	220 / 240 V - 50 Hz
Total absorption	1.2 A	1.2 A	0.8 A
Consumption	0.27 kWh / 24 h	0.19 kWh / 24 h	0.24 kWh / 24 h
Energy efficiency class	F	E	F
Annual energy consumption	99 kWh	69 kWh	88 kWh
Net machine weight	42 kg	34 kg	19 kg
Temperature range	5°C-20°C	5°C-20°C	5°C-20°C

Standard equipment: 3 sliding shelves for Vinoteca 60 (2 shelves for Bordeaux bottles - 1 shelf for Magnum bottles) / 2 sliding shelves for Vinoteca 45 (for Bordeaux bottles).

Finishes

Vinoteca is only available in black glass finish.

Assembly precautions

Make sure to leave an air gap of at least 50 mm at the back of the recessed compartment as shown in the drawing.
It is recommended to install the appliance away from heat sources, ovens or appliances generating heat or moisture. After transport, place the appliance in an upright position and wait at least 3 hours before connecting it to the electrical installation. The appliance is supplied with power supply connection cable complete with Schuko plug (length 1.30 m).

Built-in Vinoteca 60

L 595 mm
D 557 mm
H 595 mm

Built-in Vinoteca 45

L 595 mm
D 557 mm
H 455 mm

Built-in Vinoteca 15

L 595 mm
D 557 mm
H 141 mm

AIR RECIRCULATION

AIR RECIRCULATION

irinox